

Amendments to the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

1. (Currently Amended) A material spreader mounted on a truck having a chassis, said material spreader comprising:
 - a trough mounted laterally on the chassis of the truck, and
 - at least two conveying mechanisms mounted within said trough, each of said conveying mechanisms being independently driven to rotate in a desired direction and at a desired speed, wherein
 - each of said at least two conveying mechanisms is adapted to be driven in a first direction to convey material to one side of the ~~truck~~ chassis outboard of the chassis, and in a second direction to convey material to the opposite outboard side of the ~~truck~~ chassis.
2. (Original) The material spreader according to claim 1, wherein:
 - said conveying mechanisms are each independently driven by a hydraulic motor.
3. (Original) The material spreader according to claim 2, wherein:

a first one of said at least two conveying mechanisms is driven to move material in a first direction while

a second one of said at least two conveying mechanisms is driven to move material in a second direction opposite to said first direction.

4. (Previously presented) The material spreader according to claim 3, wherein:
said first conveying mechanism is driven to move material at a first speed,
and
said second conveying mechanism is driven to move material at a second speed different than said first speed.

5. (Original) The material spreader according to claim 1, wherein at least a first one of said two conveying mechanisms is an auger and is driven to rotate to move material at a first speed, and
at least a second one of said at least two conveying mechanisms is driven to move material at a second speed different than said first speed.

6. (Original) The material spreader according to claim 5, wherein said first and second conveying mechanisms are each independently driven to move by a hydraulic motor.

7. (Canceled)

8. (Original) The material spreader according to claim 1, further including:
at least one spinner positioned to receive material driven from said trough by one or more of said at least two conveying mechanisms and distribute said material in a desired pattern.
9. (Original) The material spreader according to claim 8, wherein:
at least one adjustable chute directs material from said trough to a desired point on said at least one spinner.
10. (Original) The material spreader according to claim 9, wherein said at least one adjustable chute is adjusted to a desired angle relative to said trough and said at least one spinner by changing a length of chain suspending an end of said at least one adjustable chute.
11. (Currently Amended) A method of distributing material from a truck mounted material storage container, the truck including a longitudinal conveyor for moving the material to a laterally mounted trough mounted on the chassis of the truck having at least two lateral conveyors, said method comprising:
moving material from said material storage container along said longitudinal conveyor into said trough, and independently controlling the rate of movement of said at least two lateral conveyors to distribute the material to opposite sides of said trough in a desired ratio, wherein

each of said at least two lateral conveyors is adapted to be driven in a first direction to convey material to one side of the ~~truck~~ chassis outboard of the chassis and in a second direction to convey material to the opposite outboard side of the ~~truck~~ chassis.

12. (Original) The method according to claim 11, further including:

dispensing the material from the opposite sides of said trough onto spinners that fling the material outwardly in a desired pattern.

13. (Original) The method according to claim 12, wherein the step of dispensing the material onto spinners includes adjusting the position on said spinners at which the material is deposited.

14. (Original) The method according to claim 11, wherein a first one of said at least two lateral conveyors is an auger that is rotated in a first direction at a first speed, and a second one of said at least two lateral conveyors is an auger that is rotated in a second direction at a second speed different than the first speed.

15. (Withdrawn) The method according to claim 11, wherein a first one of said at least two lateral conveyors is a belt conveyor that is moved in a first direction at a first speed, and a second one of said at least two lateral conveyors is a belt conveyor that is moved in a second direction at a second speed different than the first speed.

16. (Withdrawn) The method according to claim 11, wherein a first one of said at least two lateral conveyors is a chain conveyor that is moved in a first direction at a first speed, and a second one of said at least two lateral conveyors is a chain conveyor that is moved in a second direction at a second speed different than the first speed.

17. (Previously Presented) The material spreader according to claim 1, wherein a first one of said at least two conveying mechanisms is an auger and is driven to move material in a first direction, and a second one of said at least two conveying mechanisms is an auger and is driven to move material in a second direction different than said first direction.

18. (Withdrawn) The material spreader according to claim 1, wherein a first one of said at least two conveying mechanisms is a belt conveyor and is driven to move material in a first direction, and a second one of said at least two conveying mechanisms is a belt conveyor and is driven to move material in a second direction different than said first direction.

19. (Withdrawn) The material spreader according to claim 1, wherein a first one of said at least two conveying mechanisms is a chain conveyor and is driven to move material in a first direction, and a second one of said at least two conveying mechanisms is a chain conveyor and is driven to move material in a second direction different than said first direction.

20. (Currently Amended) A device for distributing material from a truck having a chassis and a ~~mounted~~ material storage container mounted on the chassis, comprising:

means for moving material from said material storage container in a longitudinal direction relative to said material storage container;

means for moving a first portion of said material in a first lateral direction relative to said material storage container and to one side of the chassis outboard of the chassis and depositing said first portion of said material on a first distributing means; and

means for moving a second portion of said material in a second lateral direction different from said first lateral direction relative to said material storage container and to the opposite outboard side of the chassis and depositing said second portion of said material on a second distributing means, wherein

said means for moving a first portion of said material in a first lateral direction is also adapted to move said first portion of said material in said second lateral direction, and said means for moving a second portion of said material in a second lateral direction is also adapted to move said second portion of said material in said first lateral direction.